SONY

like.no.other™

United Kingdom

This document was created on
20-Jul-2006

SDX4-200C

http://www.sony.co.uk

Ideal for fast and reliable storage of large-scale digital data and network back-up, offering data capacity of 520GB compressed (200GB native).

Variations

SDX4200C-LABEL

Features

Please be aware that the features/specifications can differ from country to country.

- High storage capacity of up to 520GB compressed data (200GB native)
- Fast data transfer using efficient Helical Scan technology, up to 24MB/sec sustained native transfer rate
- Proven reliability and durability with a 30 year media life thanks to AME II technology (Advanced Metal Evaporated)
- Quick access provided by AIT's unique Remote Memory-In-Cassette (R-MIC) incorporated into the cartridge
- Clear future Roadmap already committed up to AIT6 with a 800GB native capacity
- Available in Write-Once Read-Many (WORM) format to protect valuable data against accidental erasure and prevent alteration of archived data files

Useful Links

- Buy Online
- Where to buy
- http://www.sony.co.uk

- Cleaning tape: SDX4CL

Technical Specifications

Dimensions (nominal)	
External Width (mm)	95.0
External Height (mm)	62.5
External Depth (mm)	15.0
Weight with case (g)	79.0

Environmental requirements	
Operating Conditions (degrees F)	41~113
Operating Conditions (degrees C)	5~45
Operating Conditions (% RH)	20~80
Storage Conditions (degrees F)	41~90
Storage Conditions (degrees C)	5~32
Storage Conditions (% RH)	20~60
Record Transportation Conditions (degrees F)	-40~113
Record Transportation Conditions (degrees C)	-40~45
Record Transportation Conditions (% RH)	5~60

General Characteristics	
Magnetic material	AME II
Recording capacity (GB)	200.0

Magnetic Characteristics	
Residual magnetic flux density (mT)	500.0
Residual magnetic flux density (gauss)	5000.0

Physical Characteristics	
IC memory (Kbits)	64.0
Tape length (m)	246.0
Tape thickness (µm)	4.8
Tape width (mm)	8.0

© 2004 - 2006 Sony- Terms and Conditions | Privacy